

A5052 板

◎生地 ○片白 ●片青 △両白 ▲両青

板厚	サイズ	H32	H34	O材	参考重量 kg
0.5	1000×2000		◎		2.7
0.5	1250×2500		◎		4.2
0.6	1000×2000		◎		3.3
0.6	1220×2440		◎		4.8
0.8	1000×2000		◎		4.3
0.8	1220×2440		◎		6.4
0.8	1250×2500		◎		6.8
1	1000×2000	◎	◎		5.4
1	1220×2440	◎	◎		8
1	1250×2500	◎	◎		8.4
1	1525×3050		◎		12.7
1.2	1000×2000		◎		6.5
1.2	1220×2440	◎	◎		9.6
1.2	1250×2500		◎		10.1
1.5	1000×2000	◎	◎	◎	8.1
1.5	1220×2440	◎	◎		12
1.5	1250×2500	◎	◎		12.6
1.5	1525×3050		◎		18.7
1.6	1000×2000		◎		8.6
1.6	1220×2440		◎		12.8
2	1000×2000	◎	◎	◎	10.8
2	1220×2440	◎	◎		16
2	1250×2500	◎	◎		16.8
2	1525×3050	◎	◎		25
2.5	1000×2000	◎	◎		13.5
2.5	1220×2440		◎		20
2.5	1250×2500	◎	◎		21
3	1000×2000	◎	◎	◎	16.1
3	1220×2440	◎	◎		24
3	1250×2500	◎	◎		25.2
3	1525×3050		◎		37.5
4	1000×2000	◎	◎		21.5
4	1250×2500		◎		33.6
4	1525×3050		◎		50
5	1000×2000	◎	◎		27
5	1250×2500		◎		42
5	1525×3050		◎		62.4
6	1000×2000		◎		32.2
6	1250×2500		◎		50.3

標準在庫品以外のサイズは別途問い合わせ願います。

板厚公差

(単位：mm)

板厚公差	冷間		熱間
	0.45 を超え 0 以下	±0.09	
0.7 を超え 1 以下	±0.1		
1.1 を超え 3 以下	±0.13		
3.6 を超え 4 以下	±0.2		
4.5 を超え 5 以下	±2.5		
5 を超え 6 以下	±0.45		
6 を超え 8 以下	±0.5		

(単位：mm)

板厚公差	熱間	
	8 を超え 11 以下	±0.6
11 を超え 16 以下	±0.7	
16 を超え 22 以下	±0.8	
22 を超え 29 以下	±0.9	
29 を超え 35 以下	±1	
35 を超え 40 以下	±1.1	
40 を超え 50 以下	±1.3	